F-16C FALCON - EASYBUILD - V1.02

Designed by Nick Cara

Depron = 6mm
Wing span = 71cm (28")
Length = 104cm (41")

SETUP :-

- Weight (painted) = 356g
- Weight (painted and with battery) = 486g
- Static thrust = 650g
- Prop = 6x4
- Motor = 2000kv
- ESC = 25A minimum
- Battery = 1350mAh 3s1p 25C Li-Po (Can take up to 2170mAh)
- Radio = 3CH (or 4CH with optional rudder)
- Aileron throw = +/- 20 degrees
- Elevon throw = +/- 25 degrees
- Expo = 45%

NOTES:-

- Bevel or curve all leading edges.

3mm or 4mm Carbon rod epoxy into V slot
to wing tip)
h to wing tip)
Contr

CM
0 1 2 3 4 5 6 7 8 9 10
INCH
0 1 2 3 4
Right Aileron
Right Elevon
rol point

Trim and sand intake to a curve.
Use Hot Glue for all parts except carbon rod.
Protect lower edge of intake and lower fins with packing tape.
Connect both Ailerons and Elevons to a single pair of servos.
Paint use colours that will stand out in the sky, don't leave it white.

Doublers (For Intake)

Doublers (For Intake)

Doublers (For Intake)

Doublers (For Intake)

Battery position
COG
7cm to 8cm from wing break.
Max prop size 6”
Contro

Control point
Cut here for rudder (Optional)
Cut here for rudder (Optional)
Control point
ol point
Left Elevon
Left Aileron
MOTOR MOUNT PARTS
3mm PLYWOOD
Glue Plywood onto Depron

Intake leading edge
(Depron or Balsa)
Doublers used in corners

Doublers

Lower Front Fuse

Hatch to acces electronics and battery
Upper Fuse
Lower Rear Fuse

Control points
(Make 4 from old plastic credit card)
Tail
Cut here for rudder (Optional)
Rudder (Optional)
Control point
Rudder Servo (Optional)